



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.  
PIV Prüfinstitut Schlösser und Beschläge Velbert  
Wallstraße 41 · D 42551 Velbert  
Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:  
Andrea Horsthemke (B. Eng.)  
Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.:  
Dipl.-Ing. Stephan Schmidt  
Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69  
Mail: info@piv-velbert.de  
Es gelten unsere AGB unter: www.piv-velbert.de



1309

## Certificate of Constancy of Performance

**1309 - CPR - 0395**

(version: 03)

In accordance with the EU Regulation No 305/2011 of the European Parliament and of the Council from 09. March 2011 (Construction Products Regulation or CPR) this certificate shall apply to the construction product

**Mortise lock Forster**  
Item number: see Annex to the Certificate

placed on the market under the name or the trade name of

**Forster Profilsysteme AG**  
Amriswilerstrasse 50  
CH-9320 Arbon

and produced in the manufacturing facility

**VE 27.0395.1**

This certificate attests that all provisions of the assessment and verification of constancy of the performance according to the description in annex ZA of the standard

**EN 179:2008**

within the scope of the system 1 for the performance according to the information given in this certificate, and that

**the performance of the construction product is consistently rated as resistant.**

**Product classification key see Annex to the Certificate**

This certificate was initially created on the **04. April 2018** and shall remain valid until either the harmonized standard of the construction product, the system of assessment and verification of constancy of performance or the production conditions at the plant are changed, or suspended until the certificate of the notified certification body is suspended or revoked.

D-Velbert, 12. August 2022

This certificate has a total of 10 pages  
and replaces the certificate no. 1309-CPR-0395,  
version 02 from 22.12.2020.



*G. Röhling*  
Gregor Röhling, Dipl.-Ing. (FH)  
Deputy Head of Certification Body



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.  
 PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 · D 42551 Velbert  
 Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:  
 Andrea Horsthemke (B. Eng.)  
 Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.  
 Dipl.-Ing. Stephan Schmidt  
 Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69  
 Mail: info@piv-velbert.de  
 Es gelten unsere AGB unter: www.piv-velbert.de



1309

## Annex for the Certificate of Constancy of Performance

### 1309 - CPR - 0395

(version: 03)

Essential features	Sections of this European standard	Mandated levels and/or classes	Notes
<b>Ability for release</b> (of doors in escape routes) Release function Actuation for release Construction of the handle Double-leaf door Protruding edges and corners Installation of the handle Protrusion of the control panel Protrusion of the control elements Free end of the handle Actuating distance of the handle Test rod Actuation for release with push plate Accessible free space Free movement of the door Upward running driving bolt rods Locking counterparts Dimensions of the locking counterparts Dimensions and mass of the door External access device Release forces Requirements towards security (burglary protection)	4.2.1	none	$\leq 1 \text{ s}$ passed Type A passed $\geq 0.5 \text{ mm}$ Type A ( $X \geq 120 \text{ mm}$ ; $Z \leq 150 \text{ mm}$ ) Class 2 ( $W \leq 100 \text{ mm}$ ) $V \geq \text{c}18 \text{ mm}$ $U \geq 40 \text{ mm}$ ; $W \leq 100 \text{ mm}$ ; $\alpha \leq 30^\circ$ Type A (test block) passed NPD 20 mm passed passed passed $H \leq 15 \text{ mm}$ ; $M \leq 45^\circ$ ; $P \leq 3 \text{ mm}$ $\leq 1600 \text{ mm width}$ , $\leq 3500 \text{ mm height}$ , door mass class 7 (400 kg) passed Type A ( $\leq 70 \text{ N}$ ) Class 2 (1000 N)



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.  
 PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 · D 42551 Velbert  
 Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:  
 Andrea Horsthemke (B. Eng.)  
 Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.  
 Dipl.-Ing. Stephan Schmidt  
 Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69  
 Mail: info@piv-velbert.de  
 Es gelten unsere AGB unter: www.piv-velbert.de



1309

## Annex for the Certificate of Constancy of Performance

### 1309 - CPR - 0395

(version: 03)

Essential features	Sections of this European standard	Mandated levels and/or classes	Notes
<b>Lasting functionality in terms of the ability for release compared with aging and loss of quality</b> (for doors in escape routes) Corrosion resistance Temperature range Covers for driving bolt rods Lubrication Closing force Lasting functionality Resistance of the control element against misuse Resistance of the driving bolt rod against abuse Final examination	4.2.1	none	Class 3 (96 h, $\leq 100$ N ->type A Actuating force at $-10^{\circ}\text{C}$ and $+60^{\circ}\text{C}$ $\leq 50\%$ of the measured actuating force at $+20^{\circ}\text{C}$ NPD 20,000 cycles $\leq 50$ N Application area of the door of class A, B and D: 200,000 cycles, class 7 Application area of the door of class C: 20,000 cycles, class 7 500 N and 1000 N NPD Type A: $\leq 70$ N
<b>Ability to close automatically</b> <b>Close C</b> (of fire protection doors/smoke protection doors in escape routes) Closing force	4.2.1	none	$\leq 50$ N



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.  
 PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 · D 42551 Velbert  
 Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:  
 Andrea Horsthemke (B. Eng.)  
 Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.  
 Dipl.-Ing. Stephan Schmidt  
 Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69  
 Mail: info@piv-velbert.de  
 Es gelten unsere AGB unter: www.piv-velbert.de



1309

## Annex for the Certificate of Constancy of Performance

### 1309 - CPR - 0395

(version: 03)

Essential features	Sections of this European standard	Mandated levels and/or classes	Notes
<p><b>Lasting functionality in terms of the ability for the ability to close automatically C compared with aging and loss of quality</b>            (of fire protection doors/smoke protection doors in escape routes)</p> <p>Lasting functionality</p> <p>Closing force</p>	4.2.1	none	<p>Application area of the door of class A, B and D: 200,000 cycles, class 7            Application area of the door class C: 20,000 cycles, class 7  <math>\leq 50 \text{ N}</math></p>
<p><b>Fire resistance capabilities E (room closure) and I (thermal insulation)</b>            (of fire protection doors in escape routes)</p>	4.2.1	none	<p style="text-align: center;">Class 0            Class B:</p> <p>Fire assessment no. DMT-DO-50-423, D-Lathen from 27.07.2017            expert's report 8119231407-003-GS-BS-Kan/Kru, D-Lathen from 09.06.2022</p>
<p><b>Dangerous substances</b></p>	4.1.29 Note 2 in certification order1	none	<p style="text-align: center;">passed:</p> <p>The manufacturer declares that the product contains no hazardous substances or release them beyond the maximum levels specified in European standards and national regulations.</p>



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.  
 PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 · D 42551 Velbert  
 Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:  
 Andrea Horsthemke (B. Eng.)  
 Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.  
 Dipl.-Ing. Stephan Schmidt  
 Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69  
 Mail: info@piv-velbert.de  
 Es gelten unsere AGB unter: www.piv-velbert.de



1309

## Annex for the Certificate of Constancy of Performance

**1309 - CPR - 0395**  
(version: 03)

No.	Item-No.	Description	Function	Vs-Type	Back-set [mm]	Distance	Forend	Accessories/ Note	Classification										Cmb	Handle
									3	7	7	B*	1	3	2	2	A	B/D		
1	FO.14.250.xxxx	Sv-Panic lock	I	B/D	34-45	92 mm PZ/ 94 mm RZ	≥22 mm		3	7	7	B*	1	3	2	2	A	B/D	-	202 - 218
2	FO.14.252.xxxx.426	Sv-Panic lock with additional locking	I	B/D	34-45	92 mm PZ/ 94 mm RZ	≥22 mm	Latch 12 mm for additional locking with keep guide FO.14.321/322.1000.405/ latch 12/16 mm for additional locking with keep guide FO.14.290.0000.405	3	7	7	B*	1	3	2	2	A	B/D	-	202 - 218
3	FO.14.254.xxxx.426	Sv-Panic lock	I	A	34-45	92 mm PZ/ 94 mm RZ	≥22 mm		3	7	7	B*	1	3	2	2	A	A	13/14 29/30	202 - 218
4	FO.14.256.xxxx.426	Sv-Panic lock with additional locking	I	A	34-45	92 mm PZ/ 94 mm RZ	≥22 mm	Latch 12 mm for additional locking with keep guide FO.14.321/322.1000.405/ latch 12/16 mm for additional locking with keep guide FO.14.290.0000.405	3	7	7	B*	1	3	2	2	A	A	13/14 29/30	202 - 218
5	FO.14.260.xxxx.426	Sv-Panic lock	IVa	B/D	34-45	92 mm PZ/ 94 mm RZ	≥22 mm		3	7	7	B	1	3	2	2	A	B/D	-	202 - 218
6	FO.14.262.xxxx.426	Sv-Panic lock with additional locking	IVa	B/D	34-45	92 mm PZ/ 94 mm RZ	≥22 mm	Latch 12 mm for additional locking with keep guide FO.14.321/322.1000.405/ latch 12/16 mm for additional locking with keep guide FO.14.290.0000.405	3	7	7	B	1	3	2	2	A	B/D	-	202 - 218
7	FO.14.264.xxxx.426	Sv-Panic lock	IVa	A	34-45	92 mm PZ/ 94 mm RZ	≥22 mm		3	7	7	B	1	3	2	2	A	A	13/14 29/30	202 - 218
8	FO.14.266.xxxx.426	Sv-Panic lock with additional locking	IVa	A	34-45	92 mm PZ/ 94 mm RZ	≥22 mm	Latch 12 mm for additional locking with keep guide FO.14.321/322.1000.405/ latch 12/16 mm for additional locking with keep guide FO.14.290.0000.405	3	7	7	B	1	3	2	2	A	A	13/14 29/30	202 - 218
9	FO.14.270.xxxx.426	Sv-Panic lock	Vla	B	34-45	92 mm PZ/ 94 mm RZ	≥22 mm		3	7	7	B	1	3	2	2	A	B	-	202 - 218
10	FO.14.272.xxxx.426	Sv-Panic lock with additional locking g	Vla	B	34-45	92 mm PZ/ 94 mm RZ	≥22 mm	Latch 12 mm for additional locking with keep guide FO.14.321/322.1000.405/ latch 12/16 mm for additional locking with keep guide FO.14.290.0000.405	3	7	7	B	1	3	2	2	A	B	-	202 - 218
11	FO.14.274.xxxx.426	Sv-Panic lock	Vla	A	34-45	92 mm PZ/ 94 mm RZ	≥22 mm		3	7	7	B	1	3	2	2	A	A	13/14 29/30	202 - 218
12	FO.14.276.xxxx.426	Sv-Panic lock with additional locking	Vla	A	34-45	92 mm PZ/ 94 mm RZ	≥22 mm	Latch 12 mm for additional locking with keep guide FO.14.321/322.1000.405/ latch 12/16 mm for additional locking with keep guide FO.14.290.0000.405	3	7	7	B	1	3	2	2	A	A	13/14 29/30	202 - 218
13	FO.14.280.xxxx.426	Panic keep (Sv+200)	la	C	30-80		≥22 mm	Switch lock with guide FO.14.288.xxxx.405	3	7	7	B	1	3	2	2	A	C	3/4/ 7/8/ 11/12/ 17/18/ 21/22/ 25/26	202 - 218
14	FO.14.280xx136.426	Panic keep with rod barrier (Sv+200)	la	C	30-80		≥22 mm	Switch lock with guide FO.14.288.xxxx.405	3	7	7	0	1	3	2	2	A	C	3/4/ 7/8/ 11/12/ 17/18/ 21/22/ 25/26	202 - 218
15	FO.14.160.xxxx.426	Panic lock	I	B	29-45	92 mm PZ/ 94 mm RZ	≥22 mm		3	7	7	B*	1	3	2	2	A	B	-	202 - 218
16	FO.14.172.xxxx.426	Panic lock with additional locking	I	B	29-45	92 mm PZ/ 94 mm RZ	≥22 mm	Latch 12 mm for additional locking with keep guide FO.14.321/322.1000.405/ latch 12/16 mm for additional locking with keep guide FO.14.290.0000.405	3	7	7	B*	1	3	2	2	A	B	-	202 - 218



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.  
 PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 · D 42551 Velbert  
 Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:  
 Andrea Horsthemke (B. Eng.)  
 Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.  
 Dipl.-Ing. Stephan Schmidt  
 Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69  
 Mail: info@piv-velbert.de  
 Es gelten unsere AGB unter: www.piv-velbert.de



1309

## Annex for the Certificate of Constancy of Performance

### 1309 - CPR - 0395

(version: 03)

No.	Item-No.	Description	Function	Vs-Type	Back-set [mm]	Distance	Forend	Accessories/ Note	Classification												Cmb	Handle
									3	7	7	B*	1	3	2	2	A	A				
17	FO.14.166.xxxx.426	Panic lock	I	A	29-45	92 mm PZ/ 94 mm RZ	≥22 mm		3	7	7	B*	1	3	2	2	A	A	13/14 29/30	202 - 218		
18	FO.14.178.xxxx.426	Panic lock with additional locking	I	A	29-45	92 mm PZ/ 94 mm RZ	≥22 mm	Latch 12 mm for additional locking with keep guide FO.14.321/322.1000.405/ latch 12/16 mm for additional locking with keep guide FO.14.290.0000.405	3	7	7	B*	1	3	2	2	A	A	13/14 29/30	202 - 218		
19	FO.14.164.xxxx.426	Panic lock	IV	B	29-45	92 mm PZ/ 94 mm RZ	≥22 mm		3	7	7	B	1	3	2	2	A	B	-	202 - 218		
20	FO.14.176.xxxx.426	Panic lock with additional locking	IV	B	29-45	92 mm PZ/ 94 mm RZ	≥22 mm	Latch 12 mm for additional locking with keep guide FO.14.321/322.1000.405/ latch 12/16 mm for additional locking with keep guide FO.14.290.0000.405	3	7	7	B	1	3	2	2	A	B	-	202 - 218		
21	FO.14.170.xxxx.426	Panic lock	IV	A	29-45	92 mm PZ/ 94 mm RZ	≥22 mm		3	7	7	B	1	3	2	2	A	A	13/14 29/30	202 - 218		
22	FO.14.182.xxxx.426	Panic lock with additional locking	IV	A	29-45	92 mm PZ/ 94 mm RZ	≥22 mm	Latch 12 mm for additional locking with keep guide FO.14.321/322.1000.405/ latch 12/16 mm for additional locking with keep guide FO.14.290.0000.405	3	7	7	B	1	3	2	2	A	A	13/14 29/30	202 - 218		
23	FO.14.162.xxxx.426	Panic lock	IIIb	B	29-45	92 mm PZ/ 94 mm RZ	≥22 mm		3	7	7	B	1	3	2	2	A	B	-	202 - 218		
24	FO.14.174.xxxx.426	Panic lock with additional locking	IIIb	B	29-45	92 mm PZ/ 94 mm RZ	≥22 mm	Latch 12 mm for additional locking with keep guide FO.14.321/322.1000.405/ latch 12/16 mm for additional locking with keep guide FO.14.290.0000.405	3	7	7	B	1	3	2	2	A	B	-	202 - 218		
25	FO.14.168.xxxx.426	Panic lock	IIIb	A	29-45	92 mm PZ/ 94 mm RZ	≥22 mm		3	7	7	B	1	3	2	2	A	A	13/14 29/30	202 - 218		
26	FO.14.180.xxxx.426	Panic lock with additional locking	IIIb	A	29-45	92 mm PZ/ 94 mm RZ	≥22 mm	Latch 12 mm for additional locking with keep guide FO.14.321/322.1000.405/ latch 12/16 mm for additional locking with keep guide FO.14.290.0000.405	3	7	7	B	1	3	2	2	A	A	13/14 29/30	202 - 218		
27	FO.14.145.xxxx.426	Latch lock	-	B	29-45	92 mm PZ/ 94 mm RZ	≥22 mm		3	7	7	B	1	3	2	2	A	B	-	202 - 218		
28	FO.14.159.xxxx.426	Latch lock with additional locking	-	B	29-45	92 mm PZ/ 94 mm RZ	≥22 mm	Latch 12 mm for additional locking with keep guide FO.14.321/322.1000.405/ latch 12/16 mm for additional locking with keep guide FO.14.290.0000.405	3	7	7	B	1	3	2	2	A	B	-	202 - 218		
29	FO.14.284/ 285.xxxx.426	Panic keep with E-opener	14.284.xxxx.426 DIN right/ 14.285.xxxx.426 DIN left	la	C	34-80	≥22 mm	Switch lock with guide FO.14.288.xxxx.405/ latch suspended with guide FO.14.294.xxxx.405	3	7	7	B	1	3	2	2	A	C	3/4/ 7/8/ 11/12/ 17/18/ 21/22/ 25/26	202 - 218		
30	FO.14.284/ 285.xx136.426	Panic keep with E-opener and rod barrier	14.284.xx136.426 DIN right/ 14.285.xx136.426 DIN left	la	C	34-80	≥22 mm	Switch lock with guide FO.14.288.xxxx.405/ latch suspended with guide FO.14.294.xxxx.405	3	7	7	0	1	3	2	2	A	C	3/4/ 7/8/ 11/12/ 17/18/ 21/22/ 25/26	202 - 218		
31	FO.14.281...	Lock without latch with additional locking	Leaf width max. 1.300 mm/ Leaf height max. 2.500 mm	lb	B	30	≥24 mm	Latch 12 mm for additional locking with keep guide FO.14.321/322.1000.405/	3	6	7	B	1	3	2	2	B	B	--	203		



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.  
 PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 · D 42551 Velbert  
 Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:  
 Andrea Horsthemke (B. Eng.)  
 Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.  
 Dipl.-Ing. Stephan Schmidt  
 Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69  
 Mail: info@piv-velbert.de  
 Es gelten unsere AGB unter: www.piv-velbert.de



1309

## Annex for the Certificate of Constancy of Performance

### 1309 - CPR - 0395

(version: 03)

No.	Item-No.	Description	Function	Vs-Type	Back-set [mm]	Distance	Forend	Accessories/ Note	Classification										Cmb	Handle
32	FO.14.150...	Panic-Latch lock	IVb	B	29-45	92 mm PZ/ 94 mm RZ	≥22 mm		3	7	7	B	1	3	2	2	A	B	--	202-218
33	FO.14.151...	Panic-Latch lock without latch with additional locking	IVb	B	29-45	92 mm PZ/ 94 mm RZ	≥22 mm	Latch 12 mm for additional locking with keep guide FO.14.321/322.1000.405/ latch 12/16 mm for additional locking with keep guide FO.14.290.0000.405	3	7	7	B	1	3	2	2	A	B	--	202-218

\* - optional equipping with a secured latch locking device – necessary modification of classification:

x	x	x	0	x	x	x	x	x	x	x
---	---	---	---	---	---	---	---	---	---	---

Applies for all lock varieties: Distance 92 mm for profile cylinder  
 Distance 94 mm for round cylinder  
 Forend ≥ 22 mm

Max. weight door leaf 400 kg  
 Max. height 3.500 mm  
 Max. width 1.600 mm

Vs-Type (Device-Types)	
Vs-Type A	Device for the active leaf 2-leaf doors & for 1-leaf doors
Vs-Type B	Device for 1-leaf doors outward opening
Vs-Type C	Device for the inactive leaf 2-leaf doors
Vs-Type D	Device for 1-leaf doors inward opening

Function descriptions	
Function "I"	One-piece lock follower, permanent escape door function. It is always possible to open from the inside via the fitting. From the outside, the latch and the bolt can be retracted using the key. (Switching function E)
Function "Ia"	One-piece lock follower, permanent escape door function. It is always possible to open both leaves using the inactive leaf from the inside via the fitting. (Keep)
Function "Ib"	One-piece lock follower, permanent escape door function. It is always possible to open the door leaf from the inside via the fitting. (Keep with special function)
Function "IIIb"	Split lock follower, permanent escape door function from the inside. It is always possible to open from the inside via the fitting. The external fitting constantly has an effect on the lock latch. The bolt is only activated from the outside using the key. After an actuation from the inside, the door cannot even be opened from the outside until it is manually locked again. (Transit function D)
Function "IV"	Split lock follower, permanent escape door function from the inside. It is always possible to open from the inside via the fitting. The external fitting is constantly engaged or released using the key. The bolt is only activated from the outside using the key. After an actuation from the inside, the door cannot even be opened from the outside by means of the fitting. (Toggle function B)



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.  
 PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 · D 42551 Velbert  
 Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:  
 Andrea Horsthemke (B. Eng.)  
 Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.  
 Dipl.-Ing. Stephan Schmidt  
 Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69  
 Mail: info@piv-velbert.de  
 Es gelten unsere AGB unter: www.piv-velbert.de



1309

## Annex for the Certificate of Constancy of Performance

### 1309 - CPR - 0395

(version: 03)

Function "IVa"	Split lock follower, permanent escape door function from the inside. It is always possible to open from the inside via the fitting. In the basic position, the door locks automatically and the external fitting is released. The external fitting can be permanently engaged or released (basic position) using the key. After an actuation from the inside, the door cannot be opened from the outside by means of the fitting, when it's in the basic position. (Toggle function B)
Function "IVb"	Split lock follower, permanent escape door function from the inside without bolt. It is always possible to open from the inside via the fitting. The external fitting is permanently engaged or released by key. After an actuation from the inside, the door cannot be opened from the outside by means of the fitting. (Toggle function B)
Function "IVa"	Split lock follower, permanent escape door function from the inside. It is always possible to open from the inside via the fitting. In the basic position, the door locks automatically and the external fitting is released. The external fitting can be engaged using the key or electrically. After an actuation from the inside, the door cannot be opened from the outside by means of the fitting, when it's in the basic position. (Electric handle control EDS)

#### Approved handle sets

No.	Manufacturer	Coding
202	BKS	DO 20.10
203	ECO Schulte	DO 20.1
204	FSB	DO 20.3
205	HEWI	VE 30-26
206	Grundmann	DO 20.26
207	Dorma	DO 20.4
208	Hoppe	DO 20.x
209	Hafi	DO 20.32
210	Normbau	DO 20.18
211	Vieler	DO 20.12
212	SALTO Systems S.L.	DO 20.52
213	MEGA Gossau AG	(Item no. 33.604 and 33.603) ift No. 16-000271-PR03
214	Häfele	DO 20.10
215	Glutz	ift no. 229 PANIK-6014391-6-x
216	SimonsVoss AG	DO 20.57
217	Kaba GmbH	DO 20.31
218	Erich Dieckmann GmbH	DO 20.16





Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.  
 PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 · D 42551 Velbert  
 Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:  
 Andrea Horsthemke (B. Eng.)  
 Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.  
 Dipl.-Ing. Stephan Schmidt  
 Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69  
 Mail: info@piv-velbert.de  
 Es gelten unsere AGB unter: www.piv-velbert.de



1309

## Annex for the Certificate of Constancy of Performance

**1309 - CPR - 0395**

(version: 03)

### Approved accessories

Item-No.	Description	
FO.14.292.xxxx.426	Rod guides spring supported	for door heights above 2,50 m up to max. 3,50 m
FO.14.370.xxxx.426	Rod guides with hopper	with flat- or U-Forend
FO.14.300.xxxx.426	Striking plate, bottom	adjustable
FO.14.302.xxxx.426	Striking plate, top	for catch bolt lock and switch lock
FO.14.306/307.xxxx.426	Striking plate, top for E-opener	14.306... DIN right/ 14.307... DIN left
FO.14.321...	Latch 12 mm for additional locking with keep guide	from 35 mandrel
FO.14.322...	Latch 12 mm for additional locking with keep guide	for 30/34 mandrel
FO.14.290...	Latch 12/16 mm for additional locking with keep guide	from 30 mandrel
FO.14.288...	Switch lock with guide	for 30/34 mandrel
	Switch lock with guide	from 35 mandrel
FO.14.294...	Latch suspended with guide	for 30/34 mandrel
	Latch suspended with guide	from 35 mandrel
FO.14.324.0000.010	Locking unit, bottom	to hammering
FO.14.340.xxxx.426	Flat 270/320 x (≥22) x 3 mm	Flat 270/320 x (≥22) x 3 mm
FO.14.342.xxxx.426	U-Form 268/318 x (≥24) x (≥6) mm	U-Form 268/318 x (≥24) x (≥6) mm
FO.01.711.xxxx.426	Flat 270/320 x (≥24) x 3 mm	Flat 270/320 x (≥24) x 3 mm
FO.01.825.1500.010	Connecting rod M5 x 1.550 mm	Ø6 mm
FO.14.323.2000.010	Connecting rod M5 x 2.000 mm	Ø6 mm
FO.14.323.2500.010	Connecting rod M5 x 2.500 mm	Ø6 mm
FO.14.324.1000.010	Connecting rod M5 x 1.000 mm	Ø10 mm - for locking downward only – other lengths permitted
FO.957063/ FO.957073	Striking plate set, top, adjustable	for locking to the top and switch lock
917051/ 917052/ 917053	Rod guides Presto	
907051	Floor keep	
917028	Floor keep	
907054	Floor socket strike box	
907014	Floor socket strike box	
946023	Striking plate ITS RC2 1-flg./ GF	
946024	Striking plate ITS RC2 SF	
957065	Rod guides bottom fuego light	
957066	Rod guides bottom fuego light EI90	
917055	Striker plate adjustable	
917056	Striker plate adjustable	
947051/ 947052/ 947053	Rod guides Fuego light	



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.  
 PIV Prüfinstitut Schlösser und Beschläge Velbert  
 Wallstraße 41 · D 42551 Velbert  
 Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:  
 Andrea Horsthemke (B. Eng.)  
 Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.  
 Dipl.-Ing. Stephan Schmidt  
 Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69  
 Mail: info@piv-velbert.de  
 Es gelten unsere AGB unter: www.piv-velbert.de



1309

## Annex for the Certificate of Constancy of Performance

**1309 - CPR - 0395**

(version: 03)

Special striking plates/ Door opener / Special hardware for the external side

Alternatively to the standard strike plates, the locks can be fitted with special strike plates and electric operating-circuit door openers from the series	
<b>effeff Model series:</b>	142, 143, 131, 111, 19, 116, 118 und 119
<b>WSS-Model series:</b>	50032728, 50032729, 50032730, 50032731, 50032732, 50032733, 50032735, 50032736, 50032737, 50032738, 50032739, 50032926
<b>DORMA Model series:</b>	Fire 447, Smoke 117
<b>IST Systems Model series:</b>	FT 200, FT 201, FT 500, FT 501, R 7000, R 7001, A 7000
or optionally, with dummy strikes that are adapted to the respective door opener. When using the aforementioned door opener, it may possibly be necessary to adapt the fire protection classification (4th position of the classification key) of the locks.	
For the fittings 101 / 102/ 111/ 112, special fittings from the SALTO XS4 model series according to P-120003012 by SALTO Systems S.L. can also be used as outer fittings. The fitting must be labelled with the code DO 20.52.	

If an external access device is envisaged for use with a knob cylinder, neither the size nor the position of the knob (turning handle) can impede the actuation of the emergency exit lock.