



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.
PIV Prüfinstitut Schlösser und Beschläge Velbert
Wallstraße 41 · D 42551 Velbert
Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:
Andrea Horsthemke (B. Eng.)
Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.:
Dipl.-Ing. Stephan Schmidt
Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69
Mail: info@piv-velbert.de
Es gelten unsere AGB unter: www.piv-velbert.de



1309

Certificate of Constancy of Performance

1309 - CPR - 0396

(version: 02)

In accordance with the EU Regulation No 305/2011 of the European Parliament and of the Council from 09. March 2011 (Construction Products Regulation or CPR) this certificate shall apply to the construction product

Mortise lock Forster

Item number: see Annex to the Certificate

placed on the market under the name or the trade name of

Forster Profilsysteme AG

**Amriswilerstrasse 50
CH-9320 Arbon**

and produced in the manufacturing facility

VE 28.0396.1

This certificate attests that all provisions of the assessment and verification of constancy of the performance according to the description in annex ZA of the standard

EN 1125:2008

within the scope of the system 1 for the performance according to the information given in this certificate, and that

the performance of the construction product is consistently rated as resistant.

Product classification key see Annex to the Certificate

This certificate was initially created on the **04. April 2018** and shall remain valid until either the harmonized standard of the construction product, the system of assessment and verification of constancy of performance or the production conditions at the plant are changed, or suspended until the certificate of the notified certification body is suspended or revoked.

D-Velbert, 12. August 2022

This certificate has a total of 11 pages
and replaces the certificate no. 1309-CPR-0396,
version 01 from 22.12.2020.



G. Röhling
Gregor Röhling, Dipl.-Ing. (FH)
Deputy Head of Certification Body



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.
 PIV Prüfinstitut Schlösser und Beschläge Velbert
 Wallstraße 41 · D 42551 Velbert
 Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:
 Andrea Horsthemke (B. Eng.)
 Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.:
 Dipl.-Ing. Stephan Schmidt
 Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69
 Mail: info@piv-velbert.de
 Es gelten unsere AGB unter: www.piv-velbert.de



1309

Annex for the Certificate of Constancy of Performance

1309 - CPR - 0396

(version: 02)

Essential features	Sections of this European standard	Mandated levels and/or classes	Notes
Ability for release (of doors in escape routes)			
Release function			≤ 1 s
Attachment of the panic door lock			passed
Protruding edges and corners			≥ 0.5 mm
Double-leaf door			passed
Installation of the control rod			Z ≤ 150 mm
Length of the control rod			≥ 60%
Protrusion of the control panel			Class 1 (W ≤ 150 mm) Class 2 (W ≤ 100 mm)
End of the control rod			passed
Actuating surface of the rod			V ≥ 18 mm
Test rod			passed
Free space of the door leaf surface	4.2.1	none	R ≥ 25 mm
Accessible free space			20 mm
Free movement of the door			passed
Upward running driving bolt rods			passed
Locking counterparts			passed
Dimensions of the locking counterparts			H ≤ 15 mm; M ≤ 45°; P ≤ 3 mm
Dimensions and mass of the door			≤ 1600 mm width, ≤ 3500 mm height, door mass class 7 (400 kg)
External access device			passed
Release forces			≤ 80 N and ≤ 220 N under 1000 N pressure
Requirements towards security (burglary protection)			Class 2



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.
 PIV Prüfinstitut Schlösser und Beschläge Velbert
 Wallstraße 41 · D 42551 Velbert
 Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:
 Andrea Horsthemke (B. Eng.)
 Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.:
 Dipl.-Ing. Stephan Schmidt
 Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69
 Mail: info@piv-velbert.de
 Es gelten unsere AGB unter: www.piv-velbert.de



1309

Annex for the Certificate of Constancy of Performance

1309 - CPR - 0396

(version: 02)

Essential features	Sections of this European standard	Mandated levels and/or classes	Notes
Lasting functionality in terms of the ability for release compared with aging and loss of quality (for doors in escape routes) Corrosion resistance Temperature range Covers for driving bolt rods Lubrication Closing force Lasting functionality Resistance of the control element against misuse Resistance of the driving bolt rod against abuse Final examination	4.2.1	none	Class 3: 96 h Actuating force at -10°C and +60°C < 50% of the measured actuating force at +20°C NPD 20,000 cycles ≤ 50 N Application area of the door of class A and B: 200,000 cycles, class 7 Application area of the door of class C: 20,000 cycles, class 7 1000 N NPD ≤ 80 N and ≤ 220 N under 1000 N pressure
Ability to close automatically Close C (of fire protection doors/smoke protection doors in escape routes) Closing force	4.2.1	none	≤ 50N



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.
 PIV Prüfinstitut Schlösser und Beschläge Velbert
 Wallstraße 41 · D 42551 Velbert
 Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:
 Andrea Horsthemke (B. Eng.)
 Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.:
 Dipl.-Ing. Stephan Schmidt
 Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69
 Mail: info@piv-velbert.de
 Es gelten unsere AGB unter: www.piv-velbert.de



1309

Annex for the Certificate of Constancy of Performance

1309 - CPR - 0396

(version: 02)

Essential features	Sections of this European standard	Mandated levels and/or classes	Notes
Lasting functionality in terms of the ability for the ability to close automatically compared with aging and loss of quality (of fire protection doors/smoke protection doors in escape routes) Lasting functionality Closing force	4.2.1	none	Application area of the door of class A and B: 200,000 cycles, class 7 Application area of the door of class C: 20,000 cycles, class 7 $\leq 50N$
Fire resistance capabilities E (room closure) and I (thermal insulation) (of fire protection doors in escape routes)	4.2.1	none	Class 0 Class B: Fire assessment no. DMT-DO-50-423, D-Lathen from 27.07.2017 expert's report 8119231407-003-GS-BS-Kan/Kru, D-Lathen from 09.06.2022
Control of hazardous substances	4.1.25 ZA.1	none	passed: The manufacturer declares that the product contains no hazardous substances or release them beyond the maximum levels specified in European standards and national regulations.



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.
 PIV Prüfinstitut Schlösser und Beschläge Velbert
 Wallstraße 41 · D 42551 Velbert
 Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:
 Andrea Horsthemke (B. Eng.)
 Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.:
 Dipl.-Ing. Stephan Schmidt
 Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69
 Mail: info@piv-velbert.de
 Es gelten unsere AGB unter: www.piv-velbert.de



1309

Annex for the Certificate of Constancy of Performance

1309 - CPR - 0396

(version: 02)

No.	Item-No.	Description	Func-tion	Vs-Type	Back-set	Distance	Forend in mm	Accessories/ Note	Classification										Cmb	Bar	
									3	7	7	B*	1	3	2	1/2**	A/B	B			
1	FO.14.250.xxxx.426	Sv-Panic lock	Function "E", 1-leaf, rs/ls	I	B	34-45	92mm PZ/ 94mm RZ	≥22		3	7	7	B*	1	3	2	1/2**	A/B	B	-	101/ 111/ 121/ 131
2	FO.14.252.xxxx.426	Sv-Panic lock with additional locking		Latch 12 mm for additional locking with keep guide FO.14.321/322.../ latch 12/16 mm for additional locking with keep guide FO.14.290...	I	B	34-45	92mm PZ/ 94mm RZ	≥22		3	7	7	B*	1	3	2	1/2**	A/B	B	-
3	FO.14.254.xxxx.426	Sv-Panic lock	Function "E", 2-leaf, rs/ls	I	A	34-45	92mm PZ/ 94mm RZ	≥22		3	7	7	B*	1	3	2	1/2**	A/B	A	13/ 14 29/ 30	101/ 111/ 121/ 131
4	FO.14.256.xxxx.426	Sv-Panic lock with additional locking		Latch 12 mm for additional locking with keep guide FO.14.321/322.../ latch 12/16 mm for additional locking with keep guide FO.14.290...	I	A	34-45	92mm PZ/ 94mm RZ	≥22		3	7	7	B*	1	3	2	1/2**	A/B	A	13/ 14 29/ 30
5	FO.14.260.xxxx.426	Sv-Panic lock	Function "B", 1-leaf, rs/ls	IVa	B	34-45	92mm PZ/ 94mm RZ	≥22		3	7	7	B	1	3	2	1/2**	A/B	B	-	101/ 111/ 121/ 131
6	FO.14.262.xxxx.426	Sv-Panic lock with additional locking		Latch 12 mm for additional locking with keep guide FO.14.321/322.../ latch 12/16 mm for additional locking with keep guide FO.14.290...	IVa	B	34-45	92mm PZ/ 94mm RZ	≥22		3	7	7	B	1	3	2	1/2**	A/B	B	-
7	FO.14.264.xxxx.426	Sv-Panic lock	Function "B", 2-leaf, rs/ls	IVa	A	34-45	92mm PZ/ 94mm RZ	≥22		3	7	7	B	1	3	2	1/2**	A/B	A	13/ 14 29/ 30	101/ 111/ 121/ 131
8	FO.14.266.xxxx.426	Sv-Panic lock with additional locking		Latch 12 mm for additional locking with keep guide FO.14.321/322.../ latch 12/16 mm for additional locking with keep guide FO.14.290...	IVa	A	34-45	92mm PZ/ 94mm RZ	≥22		3	7	7	B	1	3	2	1/2**	A/B	A	13/ 14 29/ 30
9	FO.14.270.xxxx.426	Sv-Panic lock	with electronic multiple bolts, 1-leaf, rs/ls	Vla	B	34-45	92mm PZ/ 94mm RZ	≥22		3	7	7	B	1	3	2	1/2**	A/B	B	-	101/ 111/ 121/ 131
10	FO.14.272.xxxx.426	Sv-Panic lock with additional locking g		Latch 12 mm for additional locking with keep guide FO.14.321/322.../ latch 12/16 mm for additional locking with keep guide FO.14.290...	Vla	B	34-45	92mm PZ/ 94mm RZ	≥22		3	7	7	B	1	3	2	1/2**	A/B	B	-
11	FO.14.274.xxxx.426	Sv-Panic lock	with electronic multiple bolts, 2-leaf., rs/ls	Vla	A	34-45	92mm PZ/ 94mm RZ	≥22		3	7	7	B	1	3	2	1/2**	A/B	A	13/ 14 29/ 30	101/ 111/ 121/ 131
12	FO.14.276.xxxx.426	Sv-Panic lock with additional locking		Latch 12 mm for additional locking with keep guide FO.14.321/322.../ latch 12/16 mm for additional locking with keep guide FO.14.290...	Vla	A	34-45	92mm PZ/ 94mm RZ	≥22		3	7	7	B	1	3	2	1/2**	A/B	A	13/ 14 29/ 30



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.
 PIV Prüfinstitut Schlösser und Beschläge Velbert
 Wallstraße 41 · D 42551 Velbert
 Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:
 Andrea Horsthemke (B. Eng.)
 Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.:
 Dipl.-Ing. Stephan Schmidt
 Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69
 Mail: info@piv-velbert.de
 Es gelten unsere AGB unter: www.piv-velbert.de



1309

Annex for the Certificate of Constancy of Performance

1309 - CPR - 0396

(version: 02)

No.	Item-No.	Description	Function	Vs-Type	Back-set	Distance	Forend in mm	Accessories/ Note	Classification										Cmb	Bar	
									1	2	3	4	5	6	7	8	9	10			11
13	FO.14.280.xxxx.426	Panic keep (Sv+ 200)	la	C	30-80		≥22	Switch lock with guide FO.14.288...	3	7	7	B	1	3	2	1/2**	A/B	C	3/4/7/8/11/12/17/18/21/22/25/26	102/ 112/ 122/132	
14	FO.14.280.xx136.426	Panic keep with rod barrier (Sv+200)	la	C	30-80		≥22	Switch lock with guide FO.14.288...	3	7	7	0	1	3	2	1/2**	A/B	C	3/4/7/8/11/12/17/18/21/22/25/26	102/ 112/ 122/132	
15	FO.14.160.xxxx.426	Panic lock	Function "E", 1-leaf, rs/ls	I	B	29-45	92 mm PZ/ 94 mm RZ	≥22		3	7	7	B*	1	3	2	1/2**	A/B	B	-	101/ 111/ 121/131
16	FO.14.172.xxxx.426	Panic lock with additional locking		I	B	29-45	92 mm PZ/ 94 mm RZ	≥22	Latch 12 mm for additional locking with keep guide FO.14.321/322.../ latch 12/16 mm for additional locking with keep guide FO.14.290...	3	7	7	B*	1	3	2	1/2**	A/B	B	-	101/ 111/ 121/131
17	FO.14.166.xxxx.426	Panic lock	Function "E", 2-leaf, rs/ls	I	A	29-45	92 mm PZ/ 94 mm RZ	≥22		3	7	7	B*	1	3	2	1/2**	A/B	A	13/ 14 29/ 30	101/ 111/ 121/131
18	FO.14.178.xxxx.426	Panic lock with additional locking		I	A	29-45	92 mm PZ/ 94 mm RZ	≥22	Latch 12 mm for additional locking with keep guide FO.14.321/322.../ latch 12/16 mm for additional locking with keep guide FO.14.290...	3	7	7	B*	1	3	2	1/2**	A/B	A	13/ 14 29/ 30	101/ 111/ 121/131
19	FO.14.164.xxxx.426	Panic lock	Function "B", 1-leaf, rs/ls	IV	B	29-45	92 mm PZ/ 94 mm RZ	≥22		3	7	7	B	1	3	2	1/2**	A/B	B	-	101/ 111/ 121/131
20	FO.14.176.xxxx.426	Panic lock with additional locking		IV	B	29-45	92 mm PZ/ 94 mm RZ	≥22	Latch 12 mm for additional locking with keep guide FO.14.321/322.../ latch 12/16 mm for additional locking with keep guide FO.14.290...	3	7	7	B	1	3	2	1/2**	A/B	B	-	101/ 111/ 121/131
21	FO.14.170.xxxx.426	Panic lock	Function "B", 2-leaf, rs/ls	IV	A	29-45	92 mm PZ/ 94 mm RZ	≥22		3	7	7	B	1	3	2	1/2**	A/B	A	13/ 14 29/ 30	101/ 111/ 121/131
22	FO.14.182.xxxx.426	Panic lock with additional locking		IV	A	29-45	92 mm PZ/ 94 mm RZ	≥22	Latch 12 mm for additional locking with keep guide FO.14.321/322.../ latch 12/16 mm for additional locking with keep guide FO.14.290...	3	7	7	B	1	3	2	1/2**	A/B	A	13/ 14 29/ 30	101/ 111/ 121/131
23	FO.14.162.xxxx.426	Panic lock	Function "D", 1-leaf, rs/ls	IIIb	B	29-45	92 mm PZ/ 94 mm RZ	≥22		3	7	7	B	1	3	2	1/2**	A/B	B	-	101/ 111/ 121/131
24	FO.14.174.xxxx.426	Panic lock with additional locking		IIIb	B	29-45	92 mm PZ/ 94 mm RZ	≥22	Latch 12 mm for additional locking with keep guide FO.14.321/322.../ latch 12/16 mm for additional locking with keep guide FO.14.290...	3	7	7	B	1	3	2	1/2**	A/B	B	-	101/ 111/ 121/131



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.
 PIV Prüfinstitut Schlösser und Beschläge Velbert
 Wallstraße 41 · D 42551 Velbert
 Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:
 Andrea Horsthemke (B. Eng.)
 Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.:
 Dipl.-Ing. Stephan Schmidt
 Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69
 Mail: info@piv-velbert.de
 Es gelten unsere AGB unter: www.piv-velbert.de



1309

Annex for the Certificate of Constancy of Performance

1309 - CPR - 0396

(version: 02)

No.	Item-No.	Description	Function	Vs-Type	Backset	Distance	Forend in mm	Accessories/ Note	Classification										Cmb	Bar	
									3	7	7	B	1	3	2	1/2**	A/B	A			
25	FO.14.168.xxxx.426	Panic lock	IIIb	A	29-45	92mm PZ/ 94mm RZ	≥22mm		3	7	7	B	1	3	2	1/2**	A/B	A	13/ 14 29/ 30	101/ 111/ 121/ 131	
26	FO.14.180.xxxx.426	Panic lock with additional locking							Function "D", 2-leaf, rs/ls	IIIb	A	29-45	92mm PZ/ 94mm RZ	≥22mm	Latch 12 mm for additional locking with keep guide FO.14.321/322... / latch 12/16 mm for additional locking with keep guide FO.14.290...	3	7	7	B	1	3
27	FO.14.145.xxxx.426	Latch lock	-	B	29-45	92mm PZ/ 94mm RZ	≥22mm		3	7	7	B	1	3	2	1/2**	A/B	B	-	101/ 111/ 121/ 131	
28	FO.14.159.xxxx.426	Latch lock with additional locking							with transmission function, without latch, rs/ls	-	B	29-45	92mm PZ/ 94mm RZ	≥22mm	Latch 12 mm for additional locking with keep guide FO.14.321/322... / latch 12/16 mm for additional locking with keep guide FO.14.290...	3	7	7	B	1	3
29	FO.14.284/ 285.xxxx.426	Panic keep with E-opener	14.284.xxxx.426 DIN right/ 14.285.xxxx.426 DIN left	Ia	C	34-80	≥22mm		Switch lock with guide FO.14.288.../ latch suspended with guide FO.14.294...	3	7	7	B	1	3	2	1/2**	A	C	3/4/ 7/8/ 11/ 12/ 17/ 18/ 21/ 22/ 25/ 26	102/ 112/ 122/ 132
30	FO.14.284/ 285.xx136.426	Panic keep with E-opener and rod barrier								14.284.xx136.42 6 DIN right/ 14.285.xx136.42 6 DIN left	Ia	C	34-80	≥22mm	Switch lock with guide FO.14.288.../ latch suspended with guide FO.14.294	3	7	7	0	1	3
31	FO.14.281...	Lock without latch with additional locking	Leaf width max. 1.300 mm/ Leaf height max. 2.500 mm	Ib	B	30	>=24	Latch 12 mm for additional locking with keep guide FO.14.321/322...	3	6	7	B	1	3	2	2	A	B	--	101	
32	FO.14.150...	Panic-Latch lock	Function "B", without bolt, rs/ls	IVb	B	29-45	92 mm PZ/ 94 mm RZ	>=22		3	7	7	B	1	3	2	1/2**	A/B	B	--	101/ 111/ 121/131
33	FO.14.151...	Panic-Latch lock without latch with additional locking								Latch 12 mm for additional locking with keep guide FO.14.321/322.1 000.405/ latch 12/16 mm for additional locking with keep guide FO.14.290.0000.405	IVb	B	29-45	92 mm PZ/ 94 mm RZ	>=22	Latch 12 mm for additional locking with keep guide FO.14.321/322.1 000.405/ latch 12/16 mm for additional locking with keep guide FO.14.290.0000.405	3	7	7	B	1

* - optional equipping with a secured latch locking device – necessary modification of classification:

x	x	x	0	x	x	x	x	x	x
---	---	---	---	---	---	---	---	---	---

** When using panic bars no. 121-132, the 8th digit in the classification key applies:

x	x	x	x	x	x	x	1	x	x
---	---	---	---	---	---	---	---	---	---



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.
 PIV Prüfinstitut Schlösser und Beschläge Velbert
 Wallstraße 41 · D 42551 Velbert
 Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:
 Andrea Horsthemke (B. Eng.)
 Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.:
 Dipl.-Ing. Stephan Schmidt
 Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69
 Mail: info@piv-velbert.de
 Es gelten unsere AGB unter: www.piv-velbert.de



1309

Annex for the Certificate of Constancy of Performance

1309 - CPR - 0396

(version: 02)

Applies for all lock varieties: Distance 92 mm for profile cylinder
 Distance 94 mm for round cylinder
 Forend \geq 22 mm

Max. weight door leaf 400 kg
 Max. height 3.500 mm
 Max. width 1.600 mm

Vs-Type (Device-Types)	
Vs-Type A	Device for the active leaf 2-leaf doors & for 1-leaf doors
Vs-Type B	Device for 1-leaf doors outward opening
Vs-Type C	Device for the inactive leaf 2-leaf doors

Function descriptions	
Function "I"	One-piece lock follower, permanent escape door function. It is always possible to open from the inside via the fitting. From the outside, the latch and the bolt can be retracted using the key. (Switching function E)
Function "Ia"	One-piece lock follower, permanent escape door function. It is always possible to open both leaves using the inactive leaf from the inside via the fitting. (Keep)
Function "Ib"	One-piece lock follower, permanent escape door function. It is always possible to open the door leaf from the inside via the fitting. (Keep with special function)
Function "IIIb"	Split lock follower, permanent escape door function from the inside. It is always possible to open from the inside via the fitting. The external fitting constantly has an effect on the lock latch. The bolt is only activated from the outside using the key. After an actuation from the inside, the door cannot even be opened from the outside until it is manually locked again. (Transit function D)
Function "IV"	Split lock follower, permanent escape door function from the inside. It is always possible to open from the inside via the fitting. The external fitting is constantly engaged or released using the key. The bolt is only activated from the outside using the key. After an actuation from the inside, the door cannot even be opened from the outside by means of the fitting. (Toggle function B)
Function "IVa"	Split lock follower, permanent escape door function from the inside. It is always possible to open from the inside via the fitting. In the basic position, the door locks automatically and the external fitting is released. The external fitting can be permanently engaged or released (basic position) using the key. After an actuation from the inside, the door cannot be opened from the outside by means of the fitting, when it's in the basic position. (Toggle function B)
Function "IVb"	Split lock follower, permanent escape door function from the inside without bolt. It is always possible to open from the inside via the fitting. The external fitting is permanently engaged or released by key. After an actuation from the inside, the door cannot be opened from the outside by means of the fitting. (Toggle function B)
Function "VIa"	Split lock follower, permanent escape door function from the inside. It is always possible to open from the inside via the fitting. In the basic position, the door locks automatically and the external fitting is released. The external fitting can be engaged using the key or electrically. After an actuation from the inside, the door cannot be opened from the outside by means of the fitting, when it's in the basic position. (Electric handle control EDS)



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.
 PIV Prüfinstitut Schlösser und Beschläge Velbert
 Wallstraße 41 · D 42551 Velbert
 Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:
 Andrea Horsthemke (B. Eng.)
 Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.:
 Dipl.-Ing. Stephan Schmidt
 Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69
 Mail: info@piv-velbert.de
 Es gelten unsere AGB unter: www.piv-velbert.de



1309

Annex for the Certificate of Constancy of Performance

1309 - CPR - 0396

(version: 02)

Approved panic bars

No.	Designation	Type	Length of rod	Rod profile	Protection caps
101	2-907360	Panic pushbar/ Pushbar active leaf	651-800 mm length of rod	Al E4/C-0 silver coloured or stainless steel look	
	2-907361		801-950 mm length of rod		
	2-907362		951-1100 mm length of rod		
	2-907363		1101-1250 mm length of rod		
	2-907364		Special length		
102	2-907300	Panic pushbar/ Pushbar inactive leaf	651-800 mm length of rod		
	2-907301		801-950 mm length of rod		
	2-907302		951-1100 mm length of rod		
	2-907303		1101-1250 mm length of rod		
	2-907304		Special length		
111	2-907343	Pushbar Design-Line active leaf	with KS- or LM-Distance piece, 1.200 mm length of rod	Al E4/C-0 silver coloured or stainless steel look	
112	2-907345	Pushbar Design-Line inactive leaf	with KS- or LM-Distance piece, 1.200 mm length of rod	Al E4/C-0 silver coloured or stainless steel look	
121	2-907344	Pushbar Design-Line active leaf	with KS-Distance piece, 1.500 mm length of rod	Stainless steel	
122	2-907346	Pushbar Design-Line inactive leaf	with KS- Distance piece, 1.500 mm length of rod	Stainless steel	
131	ECO EPN IV 30°	Eco pushbar active leaf for PZ 92 and RZ 94 DO 20.1	up to 1.500 mm length of rod	Aluminum coated or stainless steel	
132	ECO EPN IV 45°	Eco pushbar active leaf for PZ 92 and RZ 94 DO 20.1	up to 1.500 mm length of rod	Aluminum coated or stainless steel	



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.
 PIV Prüfinstitut Schlösser und Beschläge Velbert
 Wallstraße 41 · D 42551 Velbert
 Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:
 Andrea Horsthemke (B. Eng.)
 Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.:
 Dipl.-Ing. Stephan Schmidt
 Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69
 Mail: info@piv-velbert.de
 Es gelten unsere AGB unter: www.piv-velbert.de



1309

Annex for the Certificate of Constancy of Performance

1309 - CPR - 0396

(version: 02)

Approved accessories

Item-No.	Description	
FO.14.292.xxxx.426	Rod guides spring supported	for door heights above 2,50 m up to max. 3,50 m
FO.14.370.xxxx.426	Rod guides with hopper	with flat- or U-Forend
FO.14.300.xxxx.426	Striking plate, bottom	adjustable
FO.14.302.xxxx.426	Striking plate, top	for catch bolt lock and switch lock
FO.14.306/307.xxxx.426	Striking plate, top for E-opener	14.306... DIN right/ 14.307... DIN left
FO.14.321...	Latch 12 mm for additional locking with keep guide	from 35 mandrel
FO.14.322..	Latch 12 mm for additional locking with keep guide	for 30/34 mandrel
FO.14.290...	Latch 12/16 mm for additional locking with keep guide	from 30 mandrel
FO.14.288...	Switch lock with guide	for 30/34 mandrel
	Switch lock with guide	from 35 mandrel
FO.14.294...	Latch suspended with guide	for 30/34 mandrel
	Latch suspended with guide	from 35 mandrel
FO.14.324.0000.010	Locking unit, bottom	to hammering
FO.14.340.xxxx.426	Flat 270/320 x (≥22) x 3 mm	Flat 270/320 x (≥22) x 3 mm
FO.14.342.xxxx.426	U-Form 268/318 x (≥24) x (≥6) mm	U-Form 268/318 x (≥24) x (≥6) mm
FO.01.711.xxxx.426	Flat 270/320 x (≥24) x 3 mm	Flat 270/320 x (≥24) x 3 mm
FO.01.825.1500.010	Connecting rod M5 x 1.550 mm	Ø6 mm
FO.14.323.2000.010	Connecting rod M5 x 2.000 mm	Ø6 mm
FO.14.323.2500.010	Connecting rod M5 x 2.500 mm	Ø6 mm
FO.14.324.1000.010	Connecting rod M5 x 1.000 mm	Ø10 mm - for locking downward only – other lengths permitted
FO.957063/ 957073	Striking plate set, top, adjustable	for locking to the top and switch lock
957062/ 957072	Striking plate set, adjustable	for locking to the top and switch lock
917051/ 917052/ 917053	Rod guides Presto	
907051	Floor keep	
917028	Floor keep	
907054	Floor socket strike box	
907014	Floor socket strike box	
946023	Striking plate ITS RC2 1-flg./ GF	
946024	Striking plate ITS RC2 SF	
957065	Rod guides bottom fuego light	
957066	Rod guides bottom fuego light EI90	
917055	Striker plate adjustable	
917056	Striker plate adjustable	
947051/ 947052/ 947053	Rod guides Fuego light	



Prüfinstitut der Gütegemeinschaft Schlösser und Beschläge e.V.
 PIV Prüfinstitut Schlösser und Beschläge Velbert
 Wallstraße 41 · D 42551 Velbert
 Leitung PIV Prüfinstitut Schlösser und Beschläge Velbert:
 Andrea Horsthemke (B. Eng.)
 Geschäftsführung Gütegemeinschaft Schlösser und Beschläge e.V.:
 Dipl.-Ing. Stephan Schmidt
 Telefon: +49 (0)2051/ 9506-5 · Fax : +49 (0)2051/ 9506-69
 Mail: info@piv-velbert.de
 Es gelten unsere AGB unter: www.piv-velbert.de



1309

Annex for the Certificate of Constancy of Performance

1309 - CPR - 0396

(version: 02)

Special striking plates/ Door opener / Special hardware for the external side

Alternatively to the standard strike plates, the locks can be fitted with special strike plates and electric operating-circuit door openers from the series	
effeff Model series:	142, 143, 131, 111, 19, 116, 118 and 119
WSS-Model series:	50032728, 50032729, 50032730, 50032731, 50032732, 50032733, 50032735, 50032736, 50032737, 50032738, 50032739, 50032926
DORMA Model series:	Fire 447, Smoke 117
IST Systems Model series:	FT 200, FT 201, FT 500, FT 501, R 7000, R 7001, A 7000
or optionally, with dummy strikes that are adapted to the respective door opener. When using the aforementioned door opener, it may possibly be necessary to adapt the fire protection classification (4th position of the classification key) of the locks.	
For the fittings 101 / 102/ 111/ 112, special fittings from the SALTO XS4 model series according to P-120003012 by SALTO Systems S.L. can also be used as outer fittings. The fitting must be labelled with the code DO 20.52.	

If an external access device is envisaged for use with a knob cylinder, neither the size nor the position of the knob (turning handle) can impede the actuation of the emergency exit lock.